

Product Data Sheet (PDS)

GP SYNCROGEN ATF MULTI
VEHICLE DEX III

www.generalpetroleum.de



Published By: Technical Department of General Petroleum FZE
Last Update Date: 12/12/2025

General Petroleum GmbH

GP SYNCROGEN ATF DEX III

GP SYNCROGEN ATF MULTI VEHICLE DEX III are premium quality, automatic transmission fluids made from solvent base oils, viscosity index improvers, anti-oxidants, anti-wear agents, detergents, deferments and special friction modifiers. They possess low temperature properties and low temperature fluidity as well as high shear stability meet the requirements of GM Dexron. It is recommended for modern passenger car and light trucks where DEXRON approved ATF is required.

FEATURES & BENEFITS

- Extended fluid life.
- Improved oxidation and thermal stability.
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- outstanding resistance performance against sludge and deposit formation

Outstanding low temperature performance

MEETS PERFORMANCE STANDARDS:

- **Allison C-3 & C-4, Allison TES-389B, American Motors ATF +3 (MS7176-E), Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A), BMW LA2634, BMW LT71141 (ZF 5 HP 18FL/19FL/24A), BMW ZF 5HP18FL, 5HP24, 5HP30, BMW 7045E, BMW ETL-8072B, Bosch TE-ML 09, CAT TO-2, Chrysler ATF+, +2, +3 (MS 7176E), Chrysler/Dodge/Jeep 05127382AA, Daewoo LT 71141, Esso LT 71141, Ford MERCON, Ford WSS M2C 138CJ, 166H, Ford**

XT-2-QDX (M),Ford XT-2-QSM (Syn),Ford ESP-M2C166H, XL-12,GM TASA, GM DEXRON®-II,GM DEXRON®-IID,GM DEXRON®-IIE, GM DEXRON®-IIIG,GM DEXRON®-IIIH, GM 1940700,GM 21005966, Hyundai/Kia Dex-II/ SP-II,Jaguar ATF 3403 M115, Jaguar ATF LT71141, ZF 5HP24, Jaguar ATF 3403 JLM20238, Jaguar JLM 20292,JEEP ATF+3,Mazda ATF D-II,Mazda ATF M-III,Mazda ATF F-1, MB ZF 4HP20, NAG 1 (Chrysler, Jeep, Cherokee), Opel/GM 19 40 700,Opel/GM 19 40 767, Opel/GM 21005966 Transaxle, Opel/GM 22 17466, Peugeot/Citroen Z 000169756, Peugeot/Citroen (PSA) AL4 Automatic gearbox oil (#9730.AE),Porsche ZF 5HP19FL, ZF 5HP20, LT71141, Porsche ATF 3403-M115, Porsche 000 043 205 09,Porsche 999 917 547 00 (A2),Porsche Z 000169756,PSA,Renault DPO/AL4, Renault Matic D2,Shell 3403, M115, LA 2634, Texaco 7045-E, Texaco 8072B.

GP SYNCROGEN ATF DEX III

TECHNICAL DATA

Sr. No	Characteristics	Test Method	ATF DEX III
1	APPEARANCE	VISUAL	B&C
2	COLOUR	ASTM D -1500	RED
3	DENSITY@15°C	ASTM D -1298	0.8530
4	K.VISCOSITY@40°C	ASTM D- 445	37.8
5	K.VISCOSITY@100°C	ASTM D- 445	7.00
6	VISCOSITY INDEX	ASTM D- 2270	148.3
7	FLASH POINT °C	ASTM D-92	224
8	POUR POINT °C	ASTM D-97	-39

General Petroleum GmbH

