

Product Data Sheet (PDS)

GP SYNCROGEN ATF MULTI
VEHICLE DEX VI

www.generalpetroleum.de



Published By: Technical Department of General Petroleum FZE
Last Update Date: 12/12/2025

General Petroleum GmbH

GP SYNCROGEN ATF DEX VI

GP SYNCROGEN ATF MULTI VEHICLE DEX VI is a fully synthetic transmission fluid recommended for use in passenger cars and light truck automatic transmissions that require a GM Dexron VI or earlier generation fluid. Transmissions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6, AW6A-EI, TF81SC, AF21, GA6F21WA (Mini) GP SYNCROGEN ATF MV High-ATF is a technologically advanced, high viscosity formula which imparts enhanced friction durability for smooth transmission performance and improved fuel efficiency. The superior high temperature protection extends fluid drain intervals by effectively. Resisting oxidation and thermal degradation providing extended service life transmissions. Enhanced foam control maintains responsive and reduces wear on bearings, bushings, and gears therefore extending clutch plate and band service life.

FEATURES & BENEFITS

- Improved shift performance and vehicle drivability improved shudder performance in a broad range of transmissions
 - Improved oxidation and thermal stability.
 - Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
 - outstanding resistance performance against sludge and deposit formation
- Outstanding low temperature performance

MEETS PERFORMANCE STANDARDS:

- **Acura ATF-Z1 Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1 Allison C-3 & C4 American Motors ATF +3 (MS7176-E) AML Oil No. 4G43A9A509/AA/S ATF RED 1, RED 1K Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A) Audi/VW G 052 025 A2 Audi/VW G 053 025 A2 Audi/VW G 052 162 A1/A2 Audi/VW G 055 025 A2 (JWS 3309) Audi/VW G 052 162 (ZF Lifeguard Fluid 5) (ZF No. S671 090 170) Audi/VW G 052 990 Audi/VW 052 055 BMW JWS 3309 (T-IV) BMW LA2634 BMW LT71141 (ZF 5 HP 18FL/19FL/24A) BMW ZF 5HP18FL, 5HP24, 5HP30 BMW 7045E BMW ETL 8072B BMW ATF 6 Bosch TE-ML 09 CAT TO-2 Chrysler ATF+, +2, +3 (MS7176E) Chrysler/Dodge MOPAR AS 68 RC and AS 69 RC (T-IV), JWS 3309 Chrysler/Dodge/Jeep 05127382AA Chrysler/Dodge/Jeep Borg Warner 68049954AA Daewoo LT 71141 Daihatsu AMMIX ATF D-II Daihatsu AMMIX ATF D-III SP DANA OHTM ATF (only recommend visc @ 100°C > 7.0 cSt Esso LT 71141 FIAT T-IV type, JWS 3309 Ford MERCON® Ford FNR5 (Mazda M5, XT-9- QMM5) Ford WSS M2C 138CJ, 166H Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309 Ford/Lincoln/Mercury XT-2- QDX (M) Ford/Lincoln/Mercury XT-2- QSM (Syn) Ford ESP-M2C166H, XL-12 Fuso ATF-II Fuso ATF-SPIII Fuso ATF-A4 GM9986195 (Aisin AW-1, JWS 3309) GM TASA GM DEXRON®-II GM DEXRON®-IID GM DEXRON®-**

IIE GM DEXRON®-IIIG GM DEXRON® IIH GM 1940700 GM 1940767 GM 21005966 GM 22717466 GM 88900925 GM 9986195 GM 93160393 GM Transfer Case (AutoTrak II) Hino Blue ribbon ATF Honda ATF-Z1 (except in CVTs) Honda ATF Ultra II Honda DW-1 Hyundai/Kia SP-III Hyundai/Kia Dex-II/ SP-II Hyundai/Kia JWS 3314 Hyundai/Kia 040000C90SG Hyundai/Kia NUMM040 CH20 Red-1 Hidemitsu K17 3100 PL085 ISUZU BESCO ATF-II ISUZU BESCO ATF-III ISUZU BESCO ATF SP ISUZU SCS Fluid ISUZU 08200-9001 Jaguar ATF 3403 M115, ATF 3403-M115, Jaguar ATF LT71141, ZF 5HP24 Jaguar JLM20238 Jaguar ATF 3403 JLM20238, Jaguar K17 Jaguar JLM 20292 Jaguar WSS-M2C922A1 JASO M315-2015 1A JASO M315-2015 2A JEEP ATF+3 KIA ATF SP-II, SP-III, SP-IV, SPIVM, Red 1 Land Rover LR023288 Lexus JWS 3309 MAN 339A Mazda ATF D-II Mazda ATF M-III Mazda ATF M-V Mazda ATF F-1 Mazda ATF S-1 Mazda ATF N-1 MAZDA ATF 3317 MB ZF 4HP20 MINI COOPER T-IV Mitsubishi Diaqueen SK Mitsubishi Diaqueen SP-II Mitsubishi Diaqueen SP-III Mitsubishi Diaqueen AW Mitsubishi Diaqueen J2 NAG 1 (Chrysler, Jeep, Cherokee) Nissan Matic Fluid C Nissan Matic Fluid D Nissan Matic Fluid J Nissan Matic Fluid K Nissan Matic Fluid P Opel/GM 19 40 700 Opel/GM 19 40 767 Opel/GM 21005966 Transaxle Opel/GM 22 17466 Opel/GM 88900925, Opel/GM 9986195 Peugeot ZF 4HP20 Peugeot/Citroen Z 000169756 Peugeot/Citroen (PSA) AL4 Automatic gearbox oil (#9730.AE) Porsche ZF 5HP19FL, ZF 5HP20, LT71141 Porsche ATF 3403-M115, Porsche T-IV (JWS 3309) Porsche 000 043 205 09 Porsche 999 917 547 00 (A2) Porsche 000 043 205 28 Porsche Z 000169756 PSA B71 2340 Renault DPO/AL4 Renault Matic D2 Renault Samsung SATF-D Saab T-IV (JWS 3309) Saab 93 160 393 Saturn T-IV (JWS 3309) Scion (all vehicles) Shell 3403, M115, LA 2634 Shell L 12108 Ssang yong DSIH 5M-66 Subaru ATF Subaru K0140Y0700 Subaru ATF 5AT Subaru DEXRON®-II Subaru ATF, ATF HP Subaru Opel Original ATF 09117946/93160393 Suzuki AT OIL 5D06 Suzuki ATF 2326 Suzuki ATF 2384K Suzuki JWS 3309 Suzuki ATF 3314 Suzuki ATF 3317 Texaco 7045-E Texaco 8072B Texaco N402 Toyota ATF D-II Toyota ATF D-III Toyota ATF T-III Toyota ATF T-IV Vickers M2950-S, I-286-S Voith 55.6335.xx (G607) Volvo 97325 Volvo 97335 Volvo CE 97340 Volvo PN 1161521 Volvo PN 1161540/1161640 Volvo PN 1161621 VW 5 HP (ZF 5 HP 30) VW 5HP (18FL, 30) VW 5HP (19FL, 24A) VW G-055-025 A2 (JWS 3309) VW G 052 162 (ZF Lifeguard Fluid 5) VW TL 52540-A VW TL 521 62 ZF all 3 & 4 speed transmission ZF TE-ML 05L ZF TE-ML 09 ZF TE-ML 11A, 11B ZF TE-ML 21L eMobility Claims BYD Dedicated Hybrid Transmission (DHT) Honda Immd

High Viscosity Specification.

(GP SYNCVROGEN ATF MV High-Vis ATF is technically capable in the following applications.)

American Motors ATF +4 (MS9602) BMW 7045E (83 22 0 026 922) BMW ETL-8072B (83 22 9 407 807) BMW 83 22 024 359 BMW 83 22 0403 248 BMW 83 22 0403 249 BMW 83 229 407 807 BMW 83 229 407 765 BMW 83 220 142 516 BMW 83 227 542 290 BMW 83 220 402 413 BMW 81 22 9 400 272/275 BMW 81 22 9 407 858/859 BMW 83 22 0 026 922 BMW 83 22 2 355 599 Chrysler ATF+4 (MS9602) Ford MERCON® V Ford/Lincoln/Mercury XT-5-QM (V), XT-5-DM GM 12378515 Jeep ATF +4 MAN 339 Type D MAN 339 Type F MAN 339 Type Z1 MAN 339 Type Z2 MAN 339 Type V1 MAN 339 Type V2 MB 236.1 MB 236.2 MB 236.3 MB 236.5 MB 236.6 MB 236.7 MB 236.8 MB 236.9 MB 236.10 MB 236.11 MB 236.91 Volvo CE 97342 ZF TE-ML 02F ZF TE-ML 03D ZF TE-ML 14A ZF TE-ML 14B ZF TE-ML 16L ZF TE-ML 17C.

GP SYNCROGEN ATF DEX VI

TECHNICAL DATA

Sr. No	Characteristics	Test Method	ATF DEX VI
1	APPEARANCE	VISUAL	B&C
2	COLOUR	ASTM D -1500	RED
3	DENSITY@15°C	ASTM D -1298	0.8530
4	K.VISCOSITY@40°C	ASTM D- 445	35.6
5	K.VISCOSITY@100°C	ASTM D- 445	7.00
6	VISCOSITY INDEX	ASTM D- 2270	162.135
7	FLASH POINT °C	ASTM D-92	224
8	POUR POINT °C	ASTM D-97	-39

General Petroleum GmbH

