

GP SYNCROGEN SYNTHETIC POWER STEERING FLUID



www.generalpetroleum.de

Product Data Sheet (PDS)



GP SYNCROGEN SYNTHETIC POWER STEERING FLUID

Published By:

Technical Department of
General Petroleum FZE

Last Update Date:

6/10/2025

GP SYNCROGEN SYNTHETIC POWER STEERING FLUID



GP SYNCROGEN SYNTHETIC POWER STEERING FLUID are premium quality made from synthetic base oils, antioxidants, anti-wear agents, detergents, antifoam and special friction modifiers. Power Steering Fluid delivers smoother turns, reduced steering effort, and extended system life. A high-performance hydraulic fluid designed to protect and optimize your vehicle's power steering system.

PERFORMANCE STANDARDS:

GP SYNCROGEN SYNTHETIC POWER STEERING FLUID meets and exceeds the requirements of the following specifications:

- Acura/Honda PN 08206-9002
- American Motors Corporation C4124
- Audi PN G002000
- Audi/VW G 004 012
- Bentley JNV862564F
- Bosch / ZF TE-ML 09
- Chrysler MS-11655B
- DaimlerChrysler MS1872
- DaimlerChrysler MS5931F & G
- Daimler Chrysler MS9602, ATF+4
- DaimlerChrysler MS9933A
- DaimlerChrysler MS1872
- Fendt X 902 011 622
- Ford M2C195A
- Ford M2C33F
- Ford ESW-M2C128 C&D
- Ford M2C128D
- Ford MS2195A
- Ford M2C138C
- Ford M2C138CJ
- Ford WSS M2C204A
- GM 9985010 Saginaw Power Steering Systems
- GM 9985835
- GM 89021184
- Honda
- Hyundai/Kia PSF-3
- Hyundai 00232-19017
- Iveco 18-1823
- Land Rover LR003401
- MAN M3289
- MAN, Type L1/L2
- Massey Ferguson
- Mitsubishi PS Fluid/Diamond SP III
- Navistar TMS 6810
- NH 610A
- Nissan PSF-II
- Opel B 040 0070

GP SYNCROGEN SYNTHETIC POWER STEERING FLUID



- Opel B 040 2012
- Porsche 000 043 206 56
- Porsche 000 043 203 33
- PSA B71 2710
- PSA S71 2710
- Saab 93160548
- Saab 3032 380
- Saab Power Steering Fluid 2634, 45 30 09 800, 93160548
- Saab PN 30 09 800
- SDFG OF1611S
- Subaru PN K0209A0080
- Volkswagen VW-TL-570-26
- Volkswagen VW-TL-52 146.01
- Volvo 1161529
- Volvo 30741424

FEATURES & BENEFITS:

- Advanced Anti-Wear Formula– Shields pumps and gears from wear, even under extreme pressure.
- Temperature-Resistant – Maintains optimal viscosity in both freezing cold and scorching heat.
- Anti-Foaming Technology – Prevents air bubbles for consistent, noise-free steering response.
- Corrosion & Oxidation Inhibitors – Keeps seals and hoses flexible while preventing rust and sludge buildup.

GP SYNCROGEN SYNTHETIC POWER STEERING FLUID

TECHNICAL DATA

Sr. No	Characteristics	Test Method	Results
01	APPEARANCE	VISUAL	B+C
02	COLOUR	ASTM D 1500	GOLDEN
03	DENSITY@15°C	DA-100	0.840
04	KV@40°C	ASTM D 445	37.79
05	KV@100°C	ASTM D 445	7.36
06	VISCOSITY INDEX	ASTM D 2270	165
07	FLASH POINT °C	ASTM D 92	222
08	POUR POINT °C	ASTM D 97	-48
09	CRACKLE	BUNSEN BURNER	-VE

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.